

Poly Stormer

Keep air moving efficiently across your facility with J&D's Poly Stormer. Made with high CFM in mind, this economical fan will give you the efficiency you want and the air flow you deserve.

Features

- Fan ships fully assembled and ready for installation
- Direct drive motor with no belts or bearings to maintain
- Totally enclosed, maintenance-free, highefficiency standard motors have completely sealed ball bearings. UL and CUL recognized. and are covered by a 2 Year Warranty
- Gold Star motors have a 3 Year Warranty



- Stainless steel fasteners, powder coated guards, and galvanized prop for long lasting corrosion resistance
- Light weight for easier installation
- Motors have built in automatic thermal overload protection for the longest motor life possible
- Compatible with our misting/fogging product line



All Poly Stormer fans include a hot dip galvanized mounting bracket

	Part#	Size Ph Spd			Thrust	Thrust CFM/ Watt		Prop			
	Single Phase										
	VPS36A-GS	36"	1	1	8,450	17.1	Direct	3-Glv			
	Three Phase										
:[VPS36CF-GS	36"	3	1/Var^	8,560	18.9	Direct	3-Glv			

Part#	Size	Ph	Spd	Thrust	Thrust CFM/ Watt		Prop		
Single Ph	iase								
VPS36A	36"	1	1	8,210	16.3	Direct	3-Glv		
Three Ph	Three Phase								
VPS36CF	36"	3	1	8,460	18.7	Direct	3-Glv		

* Best sellers/recommended models

^ Variable speed fans require separate variable speed control to adjust fan speed

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12

OSHA requires this fan to be mounted a minimum of 7' above the floor

High Output Deluxe Basket Fan

J&D Manufacturing's High Output Deluxe Basket Fan Series combines high performance, economical pricing and energy efficiency to give you one of the best valued fan series available on the market today.

Features

- Fan ships completely assembled and ready for installation
- Direct drive no belts or pulleys to maintain
- Heavy gauge, corrosion resistant black powder coated guards
- Single phase models include attached cord with 3-prong plug pre-wired for 115 Volts
- Guards meet OSHA 1910.212(a)(5) requirements allowing this fan to be installed at any height
- Totally enclosed, maintenance-free, high-efficiency motors feature sealed ball bearings and are covered by a 2 Year Warranty
- Compatible with our misting/fogging product line



Part#	Size	Ph	Spd	Thrust CFM	- ,	Drive	Prop		Part#	Size	Ph	Spd	Thrust CFM	,	Drive
Single P	Single Phase Three Phase														
With Cor	With Cord (pre-wired for 115V, electrician may rewire for 230V) No Cord														
VDB20	20"	1	1	3,340	9.1	Direct	3-Alm		VDB303	30"	3	1	6,730	13.0	Direct
VDB24	24"	1	1	5,370	10.8	Direct	3-Alm	*	VDB363	36"	3	1	9,500	19.4	Direct
VDB30	30"	1	1	6,500	11.4	Direct	3-Alm	;	* Best sell	ers/re	com	mend	ded mode	els	
VDB36	36"	1	1	9,520	17.3	Direct	3-Glv								
Bold red t	Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12														

	Part#	Size	Ph	Spd	Thrust CFM		Drive	Prop				
	Three Phase											
	No Cord											
	VDB303	30"	3	1	6,730	13.0	Direct	3-Alm				
*	VDB363	36"	3	1	9,500	19.4	Direct	3-Glv				
	* Bact collars/recommended models											

All High Output **Deluxe Basket** fans include a hot dip galvanized mounting bracket

▲WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.